

View Online at <https://aerobasegroup.com/nsn/5305-01-506-6573>

**Thread Class:**

3a

**Thread Length:**

0.281 inches

**Fastener Length:**

0.847 inches

**Head Style:**

Hexagon

**End Application:**

Apache attack helicopter

**Thread Diameter:**

0.250 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

3500 pounds per square inch

**Minimum Yield Strength:**

4300 pounds per square inch

**Product Name:**

Screw, captive

**Special Features:**

Material screw alloy steel 8740, per ams 6322 or equivalent, sleeve cres 304, per ams-qq-s-763; heat treatment screw harness rc 38-41, sleeve none; finish screw cadmium plate per ams qq-p-416, type ii, class 2, sleeve cadmium plate per ams-qq-p-416, type ii, class 2; thread per mil-s-8879; driver size 0.250 inch; shoulder 0.193 diameter form 0.003; head 0.475 inch dia; head cross 0.168, width 0.281, hex 0.181 inch; grip thickness 0.188-0.250 inch

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0