

View Online at <https://aerobasegroup.com/nsn/5305-01-508-2154>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.636 inches and 0.646 inches

Fastener Length:

Between 1.079 inches and 1.109 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.7556 inches and 0.7604 inches

Head Height:

Between 0.1147 inches and 0.1167 inches

Grip Diameter:

Between 0.373 inches and 0.374 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Grip Length:

Between 0.678 inches and 0.698 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Product Name:

Screw, close tolerance-assembly, 100 degree c'sunk sealing head, hi-torque, cres (125 ksi fsu), ivd aluminum coated

Material:

Stainless steel

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-83488, type 2, class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.