

View Online at <https://aerobasegroup.com/nsn/5305-01-508-6787>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Fastener Length:

Between 0.969 inches and 1.000 inches

Head Style:

Pan

Head Diameter:

Between 0.594 inches and 0.615 inches

Head Height:

Between 0.203 inches and 0.218 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340

Screw Material Specification:

Ams6322 assn standard 1st material response or ams6382 assn standard 2nd material response or mil-s-5626 military specification 2nd material response or ams6415 assn standard 3rd material response or mil-s-5000 military specification 4th material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.