NSN 5305-01-508-6787

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-508-6787 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.203 inches and 0.218 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340 **Screw Material Specification:** Ams6322 assn standard 1st material response or ams6382 assn standard 2nd material response or mil-s-5626 military specification 2nd material response or ams6415 assn standard 3rd material response or mil-s-5000 military specification 4th material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-s-5626 spec.

Mil-std (military Standard):

Fiig: A500d0