NSN 5305-01-508-9258

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-508-9258 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.176 inches and 0.196 inches **Fastener Length:** 0.312 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.078 inches and 0.088 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.199 inches and 0.219 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Recorder-moni **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 303se or steel comp 316 or steel comp 304l or steel comp 316l **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-508-9258

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0