## NSN 5305-01-508-9326



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-508-9326 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 1.157 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.623 inches and 0.633 inches **Spline Major Diameter:** Between 0.219 inches and 0.222 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Torx **End Application:** Horizontal st **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree tension head, gear drive recess-ph13-8m (125 ksi shear), inconel 718(125 ksi shear), 6al-4v titanium (95 ksi shear) Material: Nickel alloy 718 **Material Specification:** 

Ams 5662 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-508-9326

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0