NSN 5305-01-509-3247

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-509-3247 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.370 inches and 0.380 inches **Fastener Length:** Between 1.375 inches and 1.377 inches **Head Diameter:** Between 0.496 inches and 0.504 inches **Head Height:** Between 0.209 inches and 0.229 inches **Shoulder Diameter:** 0.374 inches first shoulder and 0.375 inches first shoulder **Shoulder Length:** 1.000 inches first shoulder and 1.002 inches first shoulder **Internal Drive Style:** Hexagon **End Application:** Support of pre-provisioning items for which navicp-phil acts as poe **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 **Criticality Code Justification: Shoulder Shape:** Round first shoulder **Product Name:** Scoket head shoulder screws Material: Steel comp 303 **Material Specification:** Astm-a 581 assn standard 1st material response and astm-a 582 assn standard 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-01-509-3247

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0