

View Online at <https://aerobasegroup.com/nsn/5305-01-509-8676>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.380 inches

Fastener Length:

0.630 inches

Head Style:

Knurled no. 2

Head Diameter:

0.375 inches

Head Height:

0.440 inches

Shoulder Diameter:

0.250 inches first shoulder

Shoulder Length:

0.250 inches first shoulder

Internal Drive Style:

Hexagon

End Application:

SWEE-PE-R,R-OTAR

Thread Diameter:

0.190 inches

Width Across Flats:

0.125 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

140000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Product Name:

Shoulder screw

Color:

Black threads

Material:

Steel uns k03104

Supplementary Features:

Hlength tolerances porm0.005; head chamfer is 30-45 degrees; tip chamfer is approximately 45 degrees; meets asme/ansi b18.3, class 3a unified coarse thread; shoulder is ground to highly polished finish

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0