

View Online at <https://aerobasegroup.com/nsn/5305-01-510-6740>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.453 inches

**Fastener Length:**

3.203 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.880 inches and 0.890 inches

**Grip Diameter:**

Between 0.436 inches and 0.437 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.438 inches

**Grip Length:**

2.750 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.085 inches first hole and 3.090 inches first hole

**Product Name:**

Screw-close tolerance, 100 degree countersunk, dovetail slot head, short thread, cres (125 ksi fus)

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0