NSN 5305-01-512-3976

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-3976 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.036 inches and 1.250 inches **Fastener Length:** Between 1.190 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate

170000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unrc

NSN 5305-01-512-3976

Socket Head Cap Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0