

View Online at <https://aerobasegroup.com/nsn/5305-01-512-4822>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

0.375 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.228 inches and 0.238 inches

**Head Height:**

Between 0.075 inches and 0.080 inches

**Locking Feature:**

Patch

**Internal Drive Style:**

Cross recess type ii

**End Application:**

Jsecst cst

**Thread Diameter:**

0.112 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

40

**Product Name:**

Screw, pan hd, slfse

**Screw Material:**

Steel comp 302

**Screw Material Specification:**

Astm a493, type 302hq assn standard single material response

**Screw Surface Treatment:**

Passivate and oxide

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response and mil-c-13924 mfr ref 1st treatment response

**Special Features:**

Washer-o ring material is fluorosilicone per mil-r-25988 and o-ring groove cut under head. Patch is made of polyester. Finish is black oxide.

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0