NSN 5305-01-512-5607

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-5607

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.495 inches and 0.625 inches
Fastener Length:
Between 0.595 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
End Application:
Gas gen assembly
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.187 inches and 0.190 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Curfees Treatment Chesification

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-01-512-5607

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0