## NSN 5305-01-512-8123

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-8123 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.125 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.250 inches and 0.265 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches **Second Diameter From Head:** Between 0.068 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.662 inches and 0.682 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.860 inches and 0.890 inches **Internal Drive Style:** Slot **End Application:** An/arc222 sin **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity: Product Name:** Screw, extrenally relieved body **Special Features:** All chamfered are at 45 degree, except tip end at 90 degree + - 5 degree Material: Stainless steel **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-01-512-8123

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0