NSN 5305-01-512-8293

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-8293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.430 inches **Fastener Length:** Between 1.660 inches and 1.690 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.385 inches and 0.394 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.249 inches **Point Diameter:** 0.425 inches **Point Style:** Flat **Internal Drive Style:** Torx **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree reduced head, gear drive recess **Special Features:** 125 ksi shear strength Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:**

Unjf

NSN 5305-01-512-8293

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0