## NSN 5305-01-512-8295

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-8295

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.469 inches	
Fastener Length:	
Between 1.704 inche	es and 1.734 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.438 inche	es and 0.445 inches
Spline Minor Diame	ter:
Between 0.1570 inch	nes and 0.1600 inches
Spline Major Diame	ter:
Between 0.2195 inch	nes and 0.2225 inches
Grip Diameter:	
Between 0.3110 inch	nes and 0.3120 inches
Internal Drive Style	:
Torx	
End Application:	
F18 e/f	
Thread Diameter:	
0.313 inches	
Grip Length:	
Between 1.240 inche	es and 1.260 inches
Thready Qty Per Inc	։հ (tpi)։
24	
Countersink Angle:	
Between 99.0 degree	es and 101.0 degrees
Criticality Code Jus	tification:
Agav	
Product Name:	
Bolt, 100 degree red	uced head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)
Material:	
Nickel alloy 718	
Material Specificati	on:
Ams 5662 assn stan	dard single material response
Surface Treatment:	
Passivate	
Thread Series Desi	gnator:
Unjf	

## NSN 5305-01-512-8295

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

