## NSN 5305-01-512-8299

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-8299

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.578 inches	
Fastener Length:	
Between 1.688 inches and 1.718 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.524 inches and 0.531 inches	
Spline Minor Diameter:	
Between 0.1570 inches and 0.1600 inches	
Spline Major Diameter:	
Between 0.2195 inches and 0.2225 inches	
Grip Diameter:	
Between 0.3735 inches and 0.3745 inches	
Internal Drive Style:	
Torx	
End Application:	
F18 e/f	
Thread Diameter:	
0.375 inches	
Grip Length:	
Between 1.115 inches and 1.135 inches	
Thready Qty Per Inch (tpi):	
24	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Criticality Code Justification:	
Agav	
Product Name:	
Bolt, 100 degree reduced head, gear drive recess-ph13-8mo (125 ksi shear)	, inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)
Material:	
Nickel alloy 718	
Material Specification:	
Ams 5662 assn standard single material response	
Surface Treatment:	
Passivate	
Thread Series Designator:	
Unjf	

## NSN 5305-01-512-8299

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

