

View Online at <https://aerobasegroup.com/nsn/5305-01-512-8359>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.312 inches

Fastener Length:

Between 1.579 inches and 1.609 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.464 inches and 0.473 inches

Hole Diameter:

Between 0.438 inches and 0.445 inches

Spline Major Diameter:

Between 0.154 inches and 0.156 inches

Grip Diameter:

0.312 inches

Point Diameter:

0.469 inches

Point Style:

Flat

Internal Drive Style:

Torx

End Application:

F/a-18e/f

Thread Diameter:

0.312 inches

Grip Length:

Between 1.115 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

5820 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100 degree reduced head, gear drive recess

Special Features:

125 ksi shear strength

Material:

Nickel alloy

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0