## NSN 5305-01-512-9101

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-512-9101 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.409 inches **Fastener Length:** Between 0.598 inches and 0.620 inches **Head Style:** Hexagon **Head Height:** 0.180 inches Width Between Flats: 0.375 inches **Shoulder Diameter:** 0.246 inches first shoulder and 0.248 inches first shoulder **Shoulder Length:** 0.200 inches first shoulder **Internal Drive Style:** W/o internal drive **End Application:** 1430-01-087-9844 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment:** Oxide film **Surface Treatment Specification:** Mil-c-13925, cl 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-512-9101

Shoulder Screw - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13925 spec.