## NSN 5305-01-513-1154

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-513-1154 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 1.188 inches and 1.218 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.524 inches and 0.531 inches **Spline Minor Diameter:** Between 0.1570 inches and 0.1600 inches **Spline Major Diameter:** Between 0.2195 inches and 0.2225 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Bolt, 100 degree reduced head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear) Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response

**Passivate** 

**Thread Series Designator:** 

**Surface Treatment:** 

Unjf

## NSN 5305-01-513-1154

Close Tolerance Screw - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0