NSN 5305-01-513-2377

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-513-2377 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 1.120 inches and 1.150 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.266 inches and 0.303 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches Single Shear Strength: 95000 pounds per square inch **Internal Drive Style:** Cross recess type iii **End Application:** Ac wt and cg im **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw, close tolerance **Special Features:** Cadmium plated a-286 cres screw shall be identified with green dye or paint on the thread end . coverage may include the chamfer plus one incomplete thread. Color: Green threads Material: Iron alloy 660 **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment: Cadmium

NSN 5305-01-513-2377

Close Tolerance Screw - Page 2 of 2



Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0