NSN 5305-01-513-4311

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-513-4311 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.579 inches and 0.626 inches **Head Style:** Round extended washer **Head Diameter:** 0.312 inches **Head Height:** Between 0.082 inches and 0.092 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.023 inches and 0.028 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type ii **End Application:** V-22 **Thread Diameter:** 0.1640 inches **Grip Length:** Between 0.141 inches and 0.171 inches Thready Qty Per Inch (tpi): 32 **Criticality Code Justification:** Agav **Product Name:** Screw, machine, aircraft **Special Features:** Finish - aluminum epoxy per nas4006; 160-180 ksi ftu per ams 4928 or ams 4967 Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:**

Unjc

NSN 5305-01-513-4311

Close Tolerance Screw - Page 2 of 2



		fe	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0