## NSN 5305-01-513-4311

Close Tolerance Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-513-4311

| Thread Class:  |
|--|
|  |
| 3a<br>Thread Directions  |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.438 inches   |
| Fastener Length:   |
| Between 0.579 inches and 0.626 inches  |
| Head Style:  |
| Round extended washer  |
| Head Diameter:   |
| 0.312 inches   |
| Head Height:   |
| Between 0.082 inches and 0.092 inches  |
| Extended Washer Diameter:  |
| 0.375 inches   |
| Extended Washer Thickness:   |
| Between 0.023 inches and 0.028 inches  |
| Grip Diameter:   |
| Between 0.1625 inches and 0.1635 inches  |
| Internal Drive Style:  |
| Cross recess type ii   |
| End Application:   |
| V-22   |
| Thread Diameter:   |
| 0.1640 inches  |
| Grip Length:   |
| Between 0.141 inches and 0.171 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Criticality Code Justification:  |
| Agav   |
| Product Name:  |
| Screw, machine, aircraft   |
| Special Features:  |
| Finish - aluminum epoxy per nas4006; 160-180 ksi ftu per ams 4928 or ams 4967                      |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
|  |

## **Thread Series Designator:**

Unjc

## NSN 5305-01-513-4311

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

