

View Online at <https://aerobasegroup.com/nsn/5305-01-513-4334>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.403 inches

**Fastener Length:**

1.062 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.350 inches and 0.398 inches

**Spline Major Diameter:**

0.300 inches

**Grip Diameter:**

Between 0.248 inches and 0.249 inches

**Internal Drive Style:**

Torx

**End Application:**

Emer nsn - isil

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.649 inches and 0.669 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

(inavy) screw, 100 degree six lobe reduced head, tension, close tolerance3

**Material:**

Stainless steel

**Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response or ams 5853 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0