NSN 5305-01-513-4334

N/a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-513-4334

View Online at https://aerobasegroup.com/nsn/5305-01-513-4334
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
1.062 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.350 inches and 0.398 inches
Spline Major Diameter:
0.300 inches
Grip Diameter:
Between 0.248 inches and 0.249 inches
Internal Drive Style:
Torx
End Application:
Emer nsn - isil
Thread Diameter:
0.250 inches
Grip Length:
Between 0.649 inches and 0.669 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
(inavy) screw, 100 degree six lobe reduced head, tension, close tolerance3
Material:
Stainless steel
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response or ams 5853 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

NSN 5305-01-513-4334

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0