NSN 5305-01-513-8717

Thread Class:

Right-hand

Thread Direction:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-513-8717

| Thread Length: |
|--|
| Between 0.573 inches and 0.583 inches |
| Fastener Length: |
| Between 1.813 inches and 1.843 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.749 inches and 0.760 inches |
| Spline Major Diameter: |
| Between 0.154 inches and 0.156 inches |
| Grip Diameter: |
| 0.374 inches |
| Point Diameter: |
| 0.578 inches |
| Point Style: |
| Flat |
| Internal Drive Style: |
| Torx |
| End Application: |
| Used on the fighter aircraft-first (f18 e/f) |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| Between 1.240 inches and 1.260 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Product Name: |
| Bolt, 100 degree tension head, gear drive recess |
| Special Features: |
| 125 ksi shear strength |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| |

NSN 5305-01-513-8717

Close Tolerance Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A003b0