

View Online at <https://aerobasegroup.com/nsn/5305-01-513-8731>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

Between 1.472 inches and 1.502 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.385 inches and 0.394 inches

Spline Major Diameter:

Between 0.154 inches and 0.156 inches

Grip Diameter:

0.249 inches

Point Diameter:

0.425 inches

Point Style:

Flat

Internal Drive Style:

Torx

Thread Diameter:

0.250 inches

Grip Length:

Between 1.052 inches and 1.072 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100 degree head, gear drive, recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)

Special Features:

Drilled shank, ivd aluminum coat

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0