

NSN 5305-01-513-8784 Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-513-8784 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.573 inches and 0.583 inches **Fastener Length:** Between 1.375 inches and 1.405 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.749 inches and 0.760 inches **Spline Major Diameter:** Between 0.154 inches and 0.156 inches **Grip Diameter:** 0.374 inches **Point Diameter:** 0.578 inches **Point Style:** Flat **Internal Drive Style:** Torx **End Application:** Fighter aircraft-first (f18 e/f) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.802 inches and 0.822 inches

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100 degree tension head, gear drive recess

Special Features:

125 ksi shear strength

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

NSN 5305-01-513-8784

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0