NSN 5305-01-514-1763

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-514-1763 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.611 inches and 0.641 inches **Head Style:** Flat countersunk **Head Diameter:** 0.635 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.3125 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7505 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-514-1763

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0