NSN 5305-01-514-3443

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-514-3443 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 1.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.550 inches and 0.560 inches **Spline Major Diameter:** 0.221 inches **Grip Diameter:** 0.374 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Internal Drive Style:** Torx **End Application:** F-18 aircraft **Thread Diameter:** 0.375 inches **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.260 inches first hole **Product Name:** Bolt, 100 degree reduced heard, gear drive recess-special thread length, inconel 718 (125 ksi shear) **Special Features:** Redefined head geometry Material: Nickel alloy 718 **Surface Treatment: Passivate**

Unjf

Thread Series Designator:

NSN 5305-01-514-3443

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0