Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-515-4538

Inre	ad Direction:
Right	t-hand
Thre	ad Length:
20.0	millimeters
Fast	ener Length:
20.0	millimeters
Head	l Style:
Flat o	chamfer
Heac	Diameter:
Betw	een 5.3 millimeters and 5.5 millimeters
Heac	I Height:
Betw	een 2.8 millimeters and 3.0 millimeters
Hole	Diameter:
Betw	een 1.00 millimeters and 1.14 millimeters
Inter	nal Drive Style:
Hexa	igon
Thre	ad Diameter:
3.0 n	nillimeters
Widt	h Across Flats:
Betw	een 2.52 millimeters and 2.56 millimeters
Hole	Quantity:
2	
Hole	Туре:
Drille	d
Thre	ad Pitch In Millimeters:
0.5	
Exte	rnal Thread Tolerance Class:
4h6h	
Hole	Configuration Style:
Rour	nd internal hexagon
Mate	rial:
Iron a	alloy 660
Mate	rial Specification:
Ams!	5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
mate	rial response
Surfa	ace Treatment:
Pass	ivate
Surfa	ace Treatment Specification:
Qq-p	-35 federal specification single treatment response
Thre	ad Series Designator:
Mj	
Shel	f Life:

NSN 5305-01-515-4538

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

