## NSN 5305-01-515-7167

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-515-7167 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 1.210 inches and 1.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **End Application:** V-22 aircraft **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 33.0 rockwell c and 42.0 rockwell c **Criticality Code Justification:** Agav Material: Iron alloy 660 **Material Specification:** Ms5737 assn standard single material response or ams5737 assn standard single material response **Surface Treatment Specification:** Qq-+416 federal specification single treatment response **Thread Series Designator:** Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-515-7167

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0