NSN 5305-01-515-7678

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-515-7678

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.393 inches and 0.413 inches |
| Fastener Length: |
| Between 2.013 inches and 2.043 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.464 inches |
| Grip Diameter: |
| Between 1.615 inches and 1.635 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| End Application: |
| B1-b acft |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 2.013 inches and 2.041 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| 99.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Screw |
| Special Features: |
| Internal drive ribbed |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1580 professional/industrial association standard |

NSN 5305-01-515-7678

Close Tolerance Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0