NSN 5305-01-515-7926

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-515-7926 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.393 inches and 0.413 inches **Fastener Length:** Between 1.888 inches and 1.918 inches **Head Style:** Flat countersunk **Head Diameter:** 0.464 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **End Application:** B1-b acft **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 99.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Screw **Special Features:** Internal drive ribbed Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:**

Unjf

Specification Data:

80205-nas1580 professional/industrial association standard

NSN 5305-01-515-7926

Close Tolerance Screw - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0