
## NSN 5305-01-515-7935

Close Tolerance Screw - Page 1 of 2

3a

28





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.393 inches and 0.413 inches Fastener Length: Between 1.826 inches and 1.856 inches **Head Style:** Flat countersunk **Head Diameter:** 0.464 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) **End Application:** B1-b acft **Thread Diameter:** 0.250 inches Grip Length: Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 99.0 degrees Surface Finish: 32.0 microinches threads **Product Name:** Screw **Special Features:** Internal drive ribbed Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1580 professional/industrial association standard

## NSN 5305-01-515-7935

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

