NSN 5305-01-516-1958

Shoulder Screw - Page 1 of 2

Thread Class:

2a



View Online at https://aerobasegroup.com/nsn/5305-01-516-1958

| Thread Direction: |
|--|
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| Between 0.683 inches and 0.693 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.419 inches and 0.438 inches |
| Head Height: |
| Between 0.209 inches and 0.219 inches |
| Shoulder Diameter: |
| 0.308 inches first shoulder and 0.310 inches first shoulde |
| Shoulder Length: |
| 0.245 inches first shoulder and 0.255 inches first shoulde |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Driver's vision enhancer - 12461117 |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| 0.156 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Material is stainless steel 303 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a574 assn standard single material response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-516-1958

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0