## NSN 5305-01-516-5854



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-516-5854 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Watertight **Head Diameter:** Between 0.275 inches and 0.294 inches **Head Height:** Between 0.087 inches and 0.097 inches

Internal Drive Style:

Cross recess type 1

End Application:

Rmv operator

Thread Diameter:

Tillead Diameter.

0.138 inches

**Features Provided:** 

O ring

Thready Qty Per Inch (tpi):

.... ou

32

Screw Material:

Steel comp 302

**Screw Material Specification:** 

Astm a493 assn standard single material response

**Screw Surface Treatment:** 

Oxide

**Screw Surface Treatment Specification:** 

Mil-c-13924a, cl 2 military specification single treatment response

**Special Features:** 

0-ring material-silicone rubber per zz-r-765, cl 1&2, gr70

Color:

Black

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5305-01-516-5854

Machine Screw - Page 2 of 2



Demi			

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924a spec.