NSN 5305-01-516-7230

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-516-7230 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** 0.625 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** 0.780 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.445 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.625 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Rt-179 (p)(c) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Steel comp 304l or steel comp 316l or steel comp xm-7 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

N/a

Unc

Shelf Life:

NSN 5305-01-516-7230

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0