NSN 5305-01-516-7349

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-516-7349 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** 0.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.235 inches First Diameter From Head: 0.078 inches **Second Diameter From Head:** 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.257 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.437 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Rt-179 (p)(c) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity: Special Features:** Altered item made from ms24693 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed-std-66 federal standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Mil-f-14072, type e300 military specification single treatment response

NSN 5305-01-516-7349

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.