NSN 5305-01-516-8323

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-516-8323 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.622 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.365 inches **Head Height:** 0.105 inches **First Diameter From Head:** 0.169 inches **Second Diameter From Head:** 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.272 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.372 inches **Internal Drive Style:** Slot **End Application:** Hardware **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp xm-7 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Material Specification:** Astm-a-484 assn standard single material response or astm-a-493 assn standard single material response or qq-s-763 federal specification single material response **Surface Treatment: Passivate**

Unf

Surface Treatment Specification:

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-516-8323

Externally Relieved Body Screw - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0