Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-516-8323

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

0.622 inches

Head Style:

Pan no. 2

Head Diameter:

0.365 inches

Head Height:

0.105 inches

First Diameter From Head:

0.169 inches

Second Diameter From Head:

0.140 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.272 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.372 inches

Internal Drive Style:

Slot

End Application:

Hardware

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp xm-7 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Material Specification:

Astm-a-484 assn standard single material response or astm-a-493 assn standard single material response or qq-s-763 federal specification

single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0