NSN 5305-01-517-2195

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-517-2195

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 1.3915 inches and 1.4215 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.6230 inches and 0.6335 inches
Spline Minor Diameter:
Between 0.1570 inches and 0.1600 inches
Spline Major Diameter:
Between 0.2195 inches and 0.2225 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Torx
End Application:
F18 e/f
Thread Diameter:
0.3125 inches
Grip Length:
Between 0.9275 inches and 0.9475 inches
Thready Qty Per Inch (tpi):
24
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degree tension head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5305-01-517-2195

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0