

View Online at <https://aerobasegroup.com/nsn/5305-01-517-3067>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.276 inches

**Fastener Length:**

0.463 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.258 inches and 0.305 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.187 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Nas 498 assn standard single material response or mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-a-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.