NSN 5305-01-518-6228



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-518-6228 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.072 inches and 0.079 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Hawkeye aircraft **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 60000 pounds per square inch **Product Name:** Screw, machine, fillister head, coarse thread **Screw Material:** Steel or steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response

Special Features: With self-locking element **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-518-6228

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0