## NSN 5305-01-518-6229

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-518-6229

The state of the s
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.138 inches and 0.188 inches
Fastener Length:
Between 0.156 inches and 0.188 inches
Head Style:
Fillister
Head Diameter:
Between 0.166 inches and 0.183 inches
Head Height:
Between 0.072 inches and 0.079 inches
Internal Drive Style:
Cross recess type 1
End Application:
Hawkeye aircraft
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
60000 pounds per square inch
Product Name:
Screw, machine, fillister head, coarse thread
Screw Material:
Steel or steel comp 1010
Screw Material Specification:
Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal
specification 2nd material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response
Special Features:
With self-locking element
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-518-6229

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0