NSN 5305-01-518-6738



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-518-6738 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** Between 0.156 inches and 0.188 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.055 inches and 0.062 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Hawkeye aircraft **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 600000 pounds per square inch **Product Name:** Screw, machine, fillister head, coarse thread **Screw Material:** Steel or steel comp 1010 **Screw Material Specification:** Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Special Features:** With self-locking element

Unit Of Measure:

Shelf Life:

Unc

N/a

Thread Series Designator:

NSN 5305-01-518-6738

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0