## NSN 5305-01-518-6740



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-518-6740 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.688 inches **Fastener Length:** 1.688 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.094 inches and 0.107 inches **Hole Diameter:** 0.037 inches **Internal Drive Style:** 

Slot

**End Application:** 

Hawkeye e-2c carrier

**Thread Diameter:** 

0.112 inches

**Hole Quantity:** 

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

125000 pounds per square inch

**Screw Material:** 

Steel comp 8630

**Screw Material Specification:** 

Mil-s-6050 military specification single material response

**Screw Surface Treatment:** 

Cadmium

**Screw Surface Treatment Specification:** 

Qq-p-416, type 1, class c federal specification single treatment response

**Head Hole Configuration Style:** 

Round

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

## NSN 5305-01-518-6740

Machine Screw - Page 2 of 2



H	nit	Ωf	M	eas	ur	Δ.
v		. 0	1414	-u3	uı	С.

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.