

View Online at <https://aerobasegroup.com/nsn/5305-01-518-7068>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.875 inches

Fastener Length:

Between 0.950 inches and 1.000 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.154 inches and 0.161 inches

Head Height:

Between 0.095 inches and 0.099 inches

Internal Drive Style:

Hexagon

End Application:

Seasprite helicopter

Thread Diameter:

0.099 inches

Width Across Flats:

0.078 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

180000 pounds per square inch

Minimum Yield Strength:

32000 pounds per square inch

Chamfer Angle:

Between 30.0 degrees and 45.0 degrees

Material:

Steel

Material Specification:

Ams5731 assn standard 1st material response or ams 5737 assn standard 2nd material response and ff-s-86 assn standard 3rd material response

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2411 assn standard single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Fsc Application Data:

Nha engine instl, lh and rh, k870301-009 and k870301-101

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0