NSN 5305-01-519-1369

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-519-1369 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.519 inches **Fastener Length:** 0.625 inches **Head Style:** Flat countersunk **Spline Major Diameter:** Between 0.220 inches and 0.223 inches **Internal Drive Style:** Torx **End Application:** Mv-22 aircraft (v-22 Irip 1 e-nsn isil) **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch **Criticality Code Justification:** Agav **Product Name:** Screw, 100 degree flush head, full thread, 6 lobe recess **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5835 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Ams2700method 1, type2 assn standard single treatment response or ams2700method 1, type8, class 1 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-519-1369 Machine Screw - Page 2 of 2



Fiig:

A500d0