# NSN 5305-01-519-7048

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-519-7048

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

0.427 inches

#### Fastener Length:

1.042 inches

#### Head Style:

Knurled no. 1

Head Diameter:

0.451 inches

#### Head Height:

0.590 inches

Internal Drive Style:

Hexagon

#### Material Accommodated Thickness:

Between 0.020 inches and 0.030 inches

#### **Thread Diameter:**

0.190 inches

## Width Across Flats:

Between 0.256 inches and 0.261 inches

## Thready Qty Per Inch (tpi):

32

## **Product Name:**

Turn-loc, high profile, aluminum knob, 0.031 radial float

## Material:

Stainless steel stand-off

# Material Specification:

Qq-s-763 federal specification 2nd material response stand-off or ams 5639 assn standard 2nd material response stand-off

## Surface Treatment:

Passivate stand-off

# Surface Treatment Specification:

Qq-p-35 federal specification 2nd treatment response stand-off

# Thread Series Designator:

Unf

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5305-01-519-7048

Panel Screw Assembly - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-5059 spec.

