

View Online at <https://aerobasegroup.com/nsn/5305-01-520-3818>

Thread Direction:

Right-hand

Thread Length:

Between 7.0 millimeters and 8.0 millimeters

Fastener Length:

Between 13.2 millimeters and 13.8 millimeters

Head Style:

Pan no. 2

Head Diameter:

Between 7.7 millimeters and 8.0 millimeters

Head Height:

Between 2.2 millimeters and 2.4 millimeters

Grip Diameter:

Between 3.965 millimeters and 3.990 millimeters

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

4.0 millimeters

Grip Length:

Between 5.8 millimeters and 6.2 millimeters

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Thread Pitch In Millimeters:

0.7

External Thread Tolerance Class:

4h6h

Surface Finish:

0.8 micrometers grip

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0035 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.